

## Safety Valves

### BALL TYPE SAFETY VALVES

The Maverick Ball Type Safety Valves are manufactured to the highest oilfield standards, are field proven and offer our customers dependable service.

The Maverick Safety Valve is designed for use as an inside blowout preventer for tubing and drill pipe. They are designed to stab into the top joint of tubing or drill pipe and with a 1/4 turn of the operation wrench, the valve is closed.



MAVERICK  
OILFIELD SPECIALTIES INCORPORATED

BALL TYPE SAFETY VALVES				
CONNECTION	OD	ID	TOTAL LENGTH	WEIGHT
1 1/4" CS	3 5/8"	1 3/16"	28"	50 LBS.
2 3/8" EUE	4 1/2"	2"	26"	60 LBS.
2 3/8" PH-CS		1.805"	28"	65 LBS.
2 3/8" IF		2"	26"	65 LBS.
2 7/8" IF	4 11/16"	2 1/8"	26"	65 LBS.
2 7/8" EUE	4 7/8"	2 7/16"	26"	65 LBS.
2 7/8" PH6-CS	4 7/8"	2.265"	28"	75 LBS.
3 1/2" IF	5"	2"	28"	150 LBS.
3 1/2" EUE	7"	3"	34"	200 LBS.
4 1/2" XH, IF	7"	3 1/4"	36"	200 LBS.
4 1/2" EUE	8 1/4"	4"	42"	250 LBS.

